RDE Service
TOUS CORPS D'ÉTAT
RDE Service - 2 rue Le Corbusier, 95190 Goussainville - 07 56 90 60 94 - contact@rdeservice.fr - rdeservice.fr
Prix posé et commande : https://rdeservice.fr/boutique/residentiel/

DAIKIN

SPLIT

Wall mounted unit

FTXM-A + RXM-A



BLUEVOLUTION perfera

Heat boost

Comfort+

Titanium apatite deodorising filter

Onecta via app

Multi model application

Attractive, wall mounted design with perfect indoor air quality

› Seasonal efficiency values up to A+++
› Comfort+: perfect comfort with homogeneous temperature
› 2 area motion detection sensor
› Heat boost: fast heating during start-up (pair only)
› Purifies the air of viruses, bacteria and fine dust
› Daikin Flash Streamer technology: powerful air purification
› Silver allergen removal and air purifying filter
› Voice control
› Onecta app
› Quiet in operation: down to 19dBA sound pressure level
› 3-D airflow: air is blown into all corners of a room

RDE Service
TOUS CORPS D'ÉTAT
RDE Service - 2 rue Le Corbusier, 95190 Goussainville - 07 56 90 60 94 - contact@rdeservice.fr - rdeservice.fr
Prix posé et commande : https://rdeservice.fr/boutique/residentiel/

FTXM-A + RXM-A



Indoor unit				FTXM	20A	25A	35A	42A	50A
Dimensions	Unit	HeightxWidthxDepth		mm	298 x804 x252				
Weight	Unit			kg	11.5				
Air filter	Type				Removable / washable				
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m^3/min	4.9 /6.3 /8.9 /11.9		4.6 /7.1 /9.4 /13.2	5.0 /7.2 /9.8 /13.3	5.9 /7.8 /10.4 /12.7
		Heating	Silent operation / Low / Medium / High	m^3/min	4.9 / 6.9 / 9.2 / 11.4		5.1 / 6.9 / 9.4 / 11.1	5.3 / 7.1 / 10.0 / 14.0	6.9 / 8.6 / 11.5 / 14.5
Sound power level	Cooling			dBA	54		58	60	
	Heating			dBA	53			60	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	19 /25 /41		19 /29 /45	21 /30 /45	27 /33 /46
	Heating	Silent operation/Low/High		dBA	20 /26 /39	20 /27 /39	20 /28 /39	21 /29 /45	31 /34 /46
Control systems	Infrared remote control				ARC466A86				
	Wired remote control				BRC073A1				

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m; level difference: 0m

Outdoor unit				RXM	20A	25A	35A	42A	50A
Dimensions	Unit	HeightxWidthxDepth		mm	610 x923 x367				734 x954 x401
Weight	Unit			kg	36			40	49
Sound power level	Cooling			dBA	-				
Sound pressure level	Cooling	Nom.		dBA	46		47	48	
	Heating	Nom.		dBA	47			49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~50				-10 ~50 (1) / 46 (1)
	Heating	Ambient	Min.~Max.	°CWB	-21 ~18				
Refrigerant	Type				R-32				
	GWP				675				
	Charge			kg	0.95 /-				1.10 /-
Piping connections	Liquid	OD		mm	6.4				
	Gas	OD		mm	9.5				12.7
	Piping length	OU - IU	Max.	m	20			30	
		System	Chargeless	m	10				
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)				
	Level	IU - OU	Max.	m	15			20	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240				
Current - 50Hz	Maximum fuse amps (MFA)			A	10	13			16

See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data			FTXM + RXM	20A + 20A	25A + 25A	35A + 35A	42A + 42A	50A + 50A
Cooling capacity	Nom.		kW	0.90 /2.00 /3.00	0.90 /2.50 /3.80	0.90 /3.50 /4.40	1.50 /4.20 /5.20	1.70 /5.00 /5.30
Heating capacity	Nom./Max.		kW	0.80 /2.50 /4.50	0.80 /2.80 /5.00	0.80 /4.00 /5.50	1.50 /5.40 /6.20	1.70 /5.80 /6.50
Power input	Cooling		kW	0.37	0.48	0.76	1.00	1.36
	Heating		kW	0.50	0.56	0.88	1.29	1.40
Space cooling	Energy efficiency class			A+++			A++	
	Capacity	Pdesign	kW	2.00	2.50	3.50	4.20	5.00
	SEER			9.47		9.25	8.11	7.80
	Annual energy consumption		kWh/a	74	92	132	181	224
Space heating (Average climate)	Energy efficiency class			A+++			A++	
	Capacity	Pdesign	kW	2.30	2.40	2.50	4.00	4.50
	SCOP/A			5.20			5.00	4.80
	Annual energy consumption		kWh/a	619	647	673	1,120	1,312
Nominal efficiency	EER			5.35	5.20	4.63	4.20	3.68
	COP			5.00		4.55	4.19	4.15
	Annual energy consumption		kWh	187	240	378	500	679
	Energy labeling Directive	Cooling/Heating		A/A				
Current - 50Hz	Maximum fuse amps (MFA)		A	10	13			16

(1) See separate drawing for operation range | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende

Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN24-022 02/2024

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.