RDE Service
TOUS CORPS D'ÉTAT
RDE Service - 2 rue Le Corbusier, 95190 Goussainville - 07 56 90 60 94 - contact@rdeservice.fr - rdeservice.fr
Prix posé et commande : https://rdeservice.fr/boutique/residentiel/

DAIKIN

SPLIT

Wall mounted unit

FTXTA-CW + RXTA-C



BLUEVOLUTION nepura stylish

Fireplace logic

Coanda effect - heating

Heat boost

Guaranteed operation down to -30°C

Onecta app

Where innovation meets creativity, even at ambient temperatures down to -30°C

- Guaranteed heating capacity down to -30°C
- Even temperature distribution thanks to fire place logic
- Compact design in matt crystal white
- Perfect temperature distribution thanks to Coanda effect
- Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- Onecta app
- Voice control
- Bluevolution range: lower environmental impact
- Seasonal efficiency values up to A+++ in cooling and heating
- Daikin Flash Streamer technology: powerful air purification
- Practically inaudible
- Heat boost: fast heating during start-up (pair only)

FTXTA-CW + RXTA-C



Indoor unit				FTXTA	30CW
Dimensions	Unit	HeightxWidthxDepth		mm	295 x798 x189
Weight	Unit			kg	12
Air filter	Type				Removable / washable
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m^3/min	4.9 /6.0 /9.0 /13.1
		Heating	Silent operation / Low / Medium / High	m^3/min	5.0 / 5.8 / 8.2 / 12.3
Sound power level	Cooling			dBA	60.0
	Heating			dBA	60.0
Sound pressure level	Cooling	Silent operation/Low/High		dBA	20.0 /25.0 /43.0
	Heating	Silent operation/Low/High		dBA	19.0 /24.0 /41.0
Control systems	Infrared remote control				ARC466A84
	Wired remote control				BRC073A4

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit				RXTA	30C
Dimensions	Unit	HeightxWidthxDepth		mm	605 x930 x376
Weight	Unit			kg	42
Sound power level	Cooling			dBA	60
	Heating			dBA	60
Sound pressure level	Cooling	Nom.		dBA	48.0
	Heating	Nom.		dBA	49.0
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~46
	Heating	Ambient	Min.~Max.	°CWB	-31 ~18
Refrigerant	Type				R-32
	GWP				675.0
	Charge			kg/ TCO2Eq	0.97 /0.66
Piping connections	Liquid	OD		mm	6.35
	Gas	OD		mm	9.50
	Piping length	OU - IU	Max.	m	20
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	15.0
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240
Current - 50Hz	Maximum fuse amps (MFA)			A	16

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data				FTXTA + RXTA	30CW + 30C
Cooling capacity	Min./Nom./Max.			kW	1.2 /3.0 /4.6
Heating capacity	Min./Nom./Max.			kW	0.8 /3.2 /7.10
Power input	Cooling		Nom.	kW	0.62
	Heating		Nom.	kW	0.64
Space cooling	Energy efficiency class				A+++
	Capacity		Pdesign	kW	3.00
	SEER				8.75
	Annual energy consumption			kWh/a	120
Space heating (Average climate)	Energy efficiency class				A+++
	Capacity		Pdesign	kW	3.00
	SCOP/A				5.17
	Annual energy consumption			kWh/a	812
Space heating (Cold climate)	Energy efficiency class				A+
	Capacity		Pdesignh	kW	4.38
	Annual energy consumption			kWh/a	2,248
	SCOP/C				4.09
Nominal efficiency	EER				4.89
	COP				5.01
	Annual energy consumption			kWh	310
	Energy labeling Directive		Cooling/Heating		A/A
Current - 50Hz	Maximum fuse amps (MFA)			A	16

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)

Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN23-062 08/2023

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.