RDE Service
TOUS CORPS D'ÉTAT
RDE Service - 2 rue Le Corbusier, 95190 Goussainville - 07 56 90 60 94 - contact@rdeservice.fr - rdeservice.fr
Prix posé et commande : https://rdeservice.fr/boutique/residentiel/

DAIKIN

SPLIT

Wall mounted unit

FTXZ-N + RXZ-N



BLUEVOLUTION

Ururu Sarara

Daikin Residential Controller

3 area motion detection sensor

Energy saving during standby mode

HUMIDIFY Ururu - humidification

DRY Sarara - dehumidification

Complete climate control with (de) humidification, air purification & ventilation with top efficiencies in heating & cooling

› 5 Air treatment techniques in 1
› 3 area motion detection sensor
› Daikin residential controller via app
› Voice control
› Automatic filter cleaning
› Full range A+++
› Oh so quiet
› 3-D airflow: air is blown into all corners of a room
› Award winning design

RDE Service
TOUS CORPS D'ÉTAT
RDE Service - 2 rue Le Corbusier, 95190 Goussainville - 07 56 90 60 94 - contact@rdeservice.fr - rdeservice.fr
Prix posé et commande : https://rdeservice.fr/boutique/residentiel/

FTXZ-N + RXZ-N



FTXZ-N



RXZ-N



ARC477A1

Indoor unit				FTXZ	25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth		mm		295 x798 x372	
Weight	Unit			kg		15	
Air filter	Type					Auto cleaning filter	
Fan	Air flow rate	Cooling	Silent operation/ Low/High	m^3/min	4.0 /5.3 /10.7	4.0 /5.6 /12.1	4.6 /6.6 /15.0
		Heating	Silent operation/ Low/High	m^3/min	4.8 / 6.7 / 11.7	4.8 / 6.9 / 13.3	5.9 / 7.7 / 14.4
Sound power level	Cooling			dBA	54	57	60
	Heating			dBA	56	57	59
Sound pressure level	Cooling	Silent operation/Low/ Nom./High		dBA	19 /26 /33 /38	19 /27 /35 /42	23 /30 /38 /47
	Heating	Silent operation/Low/ Nom./High		dBA	19 /28 /35 /39	19 /29 /36 /42	24 /31 /38 /44
Control systems	Infrared remote control					ARC477A1	
	Wired remote control					-	

220V | 230V | 240V | Front of heat exchanger | Back of heat exchanger

Outdoor unit				RXZ	25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth		mm		693 x795 x300	
Weight	Unit			kg		50	
Sound power level	Cooling			dBA	59	61	63
	Heating			dBA	59	61	64
Sound pressure level	Cooling	High		dBA	46	48	49
	Heating	High		dBA	46	48	50
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~43	
	Heating	Ambient	Min.~Max.	°CWB		-20 ~18	
Refrigerant	Type					R-32	
	GWP					675	
	Charge			kg/TCO2Eq		1.34 /0.9	
Piping connections	Liquid	OD		mm		6.35	
	Gas	OD		mm		9.5	
	Piping length	OU - IU	Max.	m		10	
	Level difference	IU - OU	Max.	m		8	
Power supply	Phase/Frequency/Voltage			Hz/V		1~/50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A		16	

220V | 230V | 240V | Contains fluorinated greenhouse gases

Efficiency data				FTXZ + RXZ	25N + 25N	35N + 35N	50N + 50N
Cooling capacity	Min./Nom./Max.			kW	0.6 /2.5 /3.9	0.6 /3.5 /5.3	0.6 /5.0 /5.8
Heating capacity	Min./Nom./Max.			kW	0.6 /3.6 /7.5	0.6 /5.0 /9.0	0.6 /6.3 /9.4
Power input	Cooling		Min./Nom./Max.	kW	0.11 /0.41 /0.88	0.11 /0.66 /1.33	0.11 /1.10 /1.60
	Heating		Min./Nom./Max.	kW	0.10 /0.62 /2.01	0.10 /1.00 /2.53	0.10 /1.41 /2.64
Space cooling	Energy efficiency class					A+++	
	Capacity		Pdesign	kW	2.50	3.50	5.00
	SEER				9.54	9.00	8.60
	Annual energy consumption			kWh/a	92	136	203
Space heating (Average climate)	Energy efficiency class					A+++	
	Capacity		Pdesign	kW	3.50	4.50	5.60
	SCOP/A				5.90	5.73	5.50
	Annual energy consumption			kWh/a	831	1,100	1,427
Nominal efficiency	EER				6.10 (1)	5.30 (1)	4.55 (1)
	COP				5.80 (1)	5.00 (1)	4.47 (1)
	Annual energy consumption			kWh	205	330	550
	Energy labeling Directive	Cooling/Heating				A/A	

(1) EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-021 01/2021

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.